

SD Card, real time data logger, + type K/J Temp., Patent

HOT WIRE ANEMOMETER

Model : AM-4214SD

ISO-9001, CE, IEC1010



Lutron

LUTRON ELECTRONIC

The Art of Measurement

SD Card real time data logger

HOT WIRE ANEMOMETER, + type K/J Temp.

Model : AM-4214SD

FEATURES

* Combination of hot wire and standard thermistor, deliver rapid and precise measurements even at low air velocity value.
* Slim probe, ideal for grilles & diffusers.
* Air velocity : m/s, Ft/min, Km/h, Knot, Mile/h,
* Air temperature (°C, °F)
* Air Temp. used thermistor sensor, fast response time.
* Type K, Type J thermocouple thermometer.
* Real time SD memory card Datalogger, it Built-in Clock and Calendar, real time data recorder , sampling time set from 1 second to 3600 seconds.
* Manual datalogger is available (set the sampling time to 0), during execute the manual datalogger function, it can set the different position (location) No. (position 1 to position 99).
* Innovation and easy operation, computer is not need to setup extra software, after execute datalogger, just take away the SD card from the meter and plug in the SD card into the computer, it can down load the all the measured value with the time information (year/month/date/ hour/minute/second) to the Excel directly, then user can make the further data or graphic analysis by themselves.
* SD card capacity : 1 GB to 16 GB.
* LCD with green light backlight, easy reading.
* Can default auto power off or manual power off.
* Data hold, record max. and min. reading.
* Microcomputer circuit, high accuracy.
* Power by UM3/AA (1.5 V) x 6 batteries or DC 9V adapter.
* RS232/USB PC COMPUTER interface.
* Separate probe, easy for operation of different measurement environment.
* Applications : Environmental testing, Air conveyors, Flow hoods, Clean rooms, Air velocity, Air balancing, Fans/motors/blowers, Furnace velocity, Refrigerated case, Paint spray booths.

GENERAL SPECIFICATIONS

Circuit	Custom one-chip of microprocessor LSI circuit.
Display	LCD size : 52 mm x 38 mm LCD with green backlight (ON/OFF).
Measurement Unit	<i>Air velocity:</i> m/s (meters per second) Km/h (kilometers per hour) Ft/min (FPM, feet per minute) Knots (nautical miles per hour) Mile/h (mph, miles per hour) <i>Air temperature:</i> °C, °F <i>Type K/ Type J thermometer.</i> °C, °F
Sensor Structure	<i>Air velocity :</i> Tiny glass bead thermistor. <i>Air temperature :</i> Thermistor. <i>Type K, Type J thermometer :</i> <i>Type K/J thermocouple probe.</i> <i>* Probes are optional.</i>
Datalogger Sampling Time Setting range	Auto 1 second to 3600 seconds @ Sampling time can set to 1 second, but memory data may loss. Manual Push the data logger button once will save data one time. @ Set the sampling time to 0 second. @ Manual mode, can also select the 1 to 99 position (Location) no.
Memory Card	SD memory card. 1 GB to 16 GB.
Advanced setting	* Set clock time (Year/Month/Date, Hour/Minute/ Second) * Decimal point of SD card setting * Auto power OFF management * Set beep Sound ON/OFF * Set thermometer type to Type K or Type J * Set temperature unit to °C or °F * Set sampling time * SD memory card Format
Data Hold	Freeze the display reading.
Memory Recall	Maximum & Minimum value.

Temperature Compensation	Automatic temp. compensation for the Anemometer function and the type K/J thermometer.
Sampling Time of Display	Approx. 1 second.
Data Output	RS 232/USB PC computer interface. * Connect the optional RS232 cable UPCB-02 will get the RS232 plug. * Connect the optional USB cable USB-01 will get the USB plug.
Operating Temperature	0 to 50 °C.
Operating Humidity	Less than 85% R.H.
Power Supply	* Alkaline or heavy duty DC 1.5 V battery (UM3, AA) x 6 PCs, or equivalent. * DC 9V adapter input. (AC/DC power adapter is optional).
Power Current	Normal operation (w/o SD card save data and LCD Backlight is OFF) : Approx. DC 15 mA. When SD card save the data and LCD Backlight is OFF) : Approx. DC 36 mA.
Weight	515 g/ 1.13 LB.
Dimension	<i>Main instrument :</i> 203 x 76 x 38 mm <i>Telescope Probe :</i> Round, 12 mm Dia x 280 mm (min. length). Round, 12 mm Dia x 940 mm (max. length).
Accessories Included	* Instruction manual.....1 PC * Telescope Probe.....1 PC * Hard carrying case (CA-06).....1 PC
Optional Accessories	SD Card (1 G) SD Card (2 G) Type K thermocouple probe. AC to DC 9V adapter. USB cable, USB-01. RS232 cable, UPCB-02. Data Acquisition software, SW-U801-WIN.

ELECTRICAL SPECIFICATIONS (23 ± 5 °C)

Air velocity

Measurement	Range	Resolution	Accuracy
m/s	0.2 to 5.0 m/s	0.01 m/s	± (5% + a) reading
	5.1 to 25.0 m/s	0.1 m/s	
Km/h	0.70 to 18.00 km/h	0.01 Km/h	or ± (1% + a) full scale
	18.0 to 72.0 km/h	0.1 Km/h	
Mile/h (mph)	0.50 to 11.20 mph	0.01 mph	± (1% + a) full scale
	11.2 to 44.7 mph	0.1 mph	
Knot	0.40 to 9.70 knot	0.01 Knot	± (1% + a) full scale
	9.7 to 38.8 knot	0.1 Knot	
Ft/min	40-3940 ft/min	1 Ft/min	

@ a = 0.1 m/s, 0.3 km/h, 0.2 mile/h, 0.2 knot, 20 ft/min

Note:
m/s - meters per second km/h - kilometers per hour
ft/min - feet per minute knot - nautical miles per hour
mile/h - miles per hour (international knot)

Air temperature

Measuring Range	0 °C to 50 °C / 32 °F to 122 °F
Resolution	0.1 °C / 0.1 °F
Accuracy	± 0.8 °C / 1.5 °F

Type K/J thermometer

Sensor Type	Resolution	Range	Accuracy
Type K	0.1 °C	-50.0 to 1300.0 °C	± (0.4 % + 0.5 °C)
	0.1 °F	-50.1 to -100.0 °C	± (0.4 % + 1 °C)
Type J	0.1 °C	-58.0 to 2372.0 °F	± (0.4 % + 1 °F)
	0.1 °F	-58.1 to -148.0 °F	± (0.4 % + 1.8 °F)
Type K	0.1 °C	-50.0 to 1200.0 °C	± (0.4 % + 0.5 °C)
	0.1 °F	-50.1 to -100.0 °C	± (0.4 % + 1 °C)
Type J	0.1 °C	-58.0 to 2192.0 °F	± (0.4 % + 1 °F)
	0.1 °F	-58.1 to -148.0 °F	± (0.4 % + 1.8 °F)

PATENT	CHINA : ZL 2008 2 0189918.5 ZL 2008 2 0189917.0 Germany : Nr. 20 2008 016 337.4 JAPAN : 3151214	TAIWAN : M 456490 U.S.A. : Pending
--------	--	---------------------------------------

* Appearance and specifications listed in this brochure are subject to change without notice.

1605-AM4214SD