

*SD card real time data recorder
4 to 20 mA output*

SOUND LEVEL DATA RECORDER

Model : MSL-388SD

ISO-9001, CE, IEC1010



LUTRON ELECTRONIC

The Art of Measurement

**SD card real time data recorder
4 to 20 mA output**

SOUND LEVEL DATA RECORDER

Model : MSL-388SD

FEATURES

* Frequency and Time weighting are designed to meet IEC 61672 class 2.
* A & C weighting networks comply with standards.
* LCD is dot-matrix with backlight and easy reading.
* Data-logger and Sound level meter.
* 0.5" standard microphone head.
* Time weighting (Fast & Slow) dynamic characteristic modes.
* Condenser microphone for high accuracy & long-term stability.
* Memory function to store the Max. & Min. value.
* Hold functions.
* Real time Datalogger Records device of an external memory device (SD memory card), Real time Datalogger, it Built-in Clock and Calendar, real time data recorder, sampling time set from 5,10,30,60,120,300,600,1800,3600 seconds.
* Manual datalogger is available (set the sampling time to 0 second).
* Innovation and easy operation, computer is not need to setup extra software, after execute datalogger, just take away the SD card from the meter and plug in the SD card into the computer, it can download the all the measured value with the time information (year/month/date/ hour/minute/second) to the Excel directly, then user can make the further data or graphic analysis by themselves.
* SD card capacity : 1 GB to 16 GB.
* Can default auto power off or manual power off.
* 4-20 mA analog output.
* Microcomputer circuit, high accuracy.
* Power by UM4/AAA (1.5 V) x 6 batteries or DC 9V adapter.
* RS232/USB PC COMPUTER interface.
* Heavy duty & compact housing case.

SPECIFICATIONS

Circuit	Custom one-chip of microprocessor LSI circuit.																		
Display	LCD size : 50 mm x 30 mm LCD with green backlight (ON/OFF).																		
Measurement Type	SPL : Sound pressure level																		
Measurement Range	SPL : 30-80,50-100,80-130 , Auto 30 - 130 dB.																		
Resolution	0.1 dB.																		
Function	dB (A & C frequency weighting), Time weighting (Fast, Slow), Data hold Record (Max., Min.).																		
Accuracy (23 ± 5 °C)	Characteristics of " A " frequency weighting network meet IEC 61672 class 2. Under 94 dB input signal, the accuracy are : <table border="1" data-bbox="343 1451 576 1659"> <tr><td>31.5 Hz</td><td>± 3.5 dB</td></tr> <tr><td>63 Hz</td><td>± 2.5 dB</td></tr> <tr><td>125 Hz</td><td>± 2.0 dB</td></tr> <tr><td>250 Hz</td><td>± 1.9 dB</td></tr> <tr><td>500 Hz</td><td>± 1.9 dB</td></tr> <tr><td>1 K Hz</td><td>± 1.4 dB</td></tr> <tr><td>2 K Hz</td><td>± 2.6 dB</td></tr> <tr><td>4 K Hz</td><td>± 3.6 dB</td></tr> <tr><td>8 K Hz</td><td>± 5.6 dB</td></tr> </table>	31.5 Hz	± 3.5 dB	63 Hz	± 2.5 dB	125 Hz	± 2.0 dB	250 Hz	± 1.9 dB	500 Hz	± 1.9 dB	1 K Hz	± 1.4 dB	2 K Hz	± 2.6 dB	4 K Hz	± 3.6 dB	8 K Hz	± 5.6 dB
31.5 Hz	± 3.5 dB																		
63 Hz	± 2.5 dB																		
125 Hz	± 2.0 dB																		
250 Hz	± 1.9 dB																		
500 Hz	± 1.9 dB																		
1 K Hz	± 1.4 dB																		
2 K Hz	± 2.6 dB																		
4 K Hz	± 3.6 dB																		
8 K Hz	± 5.6 dB																		
Frequency Weighting Network	Characteristics of A & C. A weighting : The characteristic is simulated as "Human Ear Listing" response. Typical, if making the environmental sound level measurement, always select to A weighting. C weighting : The characteristic is near the "FLAT" response. Typical, it is suitable for checking the noise of machinery (Q.C. check) & knowing the sound pressure level of the tested equipment.																		
Data hold	To freeze the measurement value.																		

Time weighting (FAST & SLOW)	Fast - t = 125 ms * "Fast" range is simulated the human ear response time weighting. Slow - t = 1 s * "Slow" range is easy to get the average values of vibration sound level.
Function selector SPL	range : 30-80dB, 50-100dB, 80-130dB Auto range : 30~130dB.
Frequency	31.5 to 8,000 Hz.
Microphone type	Electric condenser microphone.
Microphone size	Out size, 12.7 mm DIA. (1/2 inch).
Calibration VR	Build in external calibration (key), easy to calibrate on 94 dB level by key button. * Calibrated via external SOUND CALIBRATOR (SC-941, SC-942, optional).
Calibrator	B & K (Bruel & kjaer), MULTIFUNCTION ACOUSTIC CALIBRATOR Type 4226.
Datalogger Sampling Time Setting range	Auto 5,10,30,60,120,300,600,1800,3600 seconds @ Sampling time can set to 1 second, but memory data may loss. Manual Push the data logger button once will save data one time. @ Set the sampling time to 0 second.
Memory device	external memory device (AC Adapter only) : SD memory card. 1 GB to 16 GB.
Advanced setting	* Set clock time (Year/Month/Date,Hour/Minute/ Second) * Set sampling time * Auto power OFF management * Set beep Sound ON/OFF * Decimal point of SD card setting * SD memory card Format
Over Indication	Show " - - - - ".
Data Hold	Freeze the display reading.
Memory Recall	Maximum & Minimum value.
Sampling Time of Display	Approx. 1 second.
Data Output	RS 232/USB PC computer interface. * Connect the optional RS232 cable, UPCB-02 will get the RS232 plug. * Connect the optional USB cable, USB-01 will get the USB plug.
Power off	Auto shut off saves battery life or manual off by push button.
Operating Temperature	0 to 50 °C .
Operating Humidity	Less than 85% R.H.
Power Supply	* Alkaline or heavy duty DC 1.5 V battery (UM4, AAA) x 6 PCs, or equivalent. * DC 9V adapter input. (AC/DC power adapter is optional).
Power Current	Normal operation (w/o SD card save data and LCD Backlight is OFF) : Approx. DC 16 mA. When SD card save the data but and LCD Backlight is OFF) : Approx. DC 16 mA. * ,if LCD backlight on, the power consumption will increase approx. DC 8 mA.
Weight	250 g/ 0.55 LB. (without battery)
Dimension	132 x 80 x 32 mm. (5.2 x 3.1 x 1.3 inch).
Accessories Included	* Instruction manual.....1 PC * Plug of 4 to 20 mA output (SKT-AS385)..... 1 PC * Microphone with clip..... 1 PC * AC to DC 9V adapter..... 1 PC
Optional Accessories	* Sound calibrator (94 dB), SC-941. * Sound calibrator (94/114 dB), SC-942. * Sound wind shield ball, SB-01 * SD Card. * USB cable, USB-01. * RS232 cable, UPCB-02. * Data Acquisition software, SW-U801-WIN. * Excel data Acquisition software, SW-E802.

* Appearance and specifications listed in this brochure are subject to change without notice.

1804-MSL388SD