

Oxidation reduction potential electrode

ORP ELECTRODE

Model : ORP-15

ISO-9001, CE, IEC1010



FEATURES

- * Professional ORP electrode with high accuracy and extreme reliability.
- * Silver-silver/chloride reference gel.
- * Epoxy body, BNC connector and 2 meters cable.
- * 12.3 mm Dia, x 150 mm length.
- * Range : -2,000 to 2,000 mV.
- * To cooperate LUTRON all ORP meters, application for water conditioning, aquariums, beverage, fish hatcheries, food processing, photography, laboratory , paper industry, quality control.



Lutron

LUTRON ELECTRONIC

The Art of Measurement

ORP ELECTRODE

Model : ORP-15

Electrode Structure	Silver-silver/chloride reference gel.	
Measurement range	-2,000 mV to +2,000 mV.	
Measuring Temperature	0 to 65 °C (32 to 149 °F).	
Body Material	Epoxy.	
Connector	BNC connector with twin fiber junction, platinum wire pin.	
Mechanical Protection	With protection bottle on the electrode head.	
Dimensions	Body length	150 mm.
	Body Dia.	12 mm.
	Cable length	2000 mm.

* Appearance and specifications listed in this brochure are subject to change without notice. 1709-ORRP15