

4 in 1, + Dew point

ANEMOMETER, HUMIDITY/TEMP.

Model : SP-82AH

ISO-9001, CE, IEC1010



Lutron

LUTRON ELECTRONIC

The Art of Measurement

4 in 1

ANEMOMETER HUMIDITY/TEMP. METER

Model : SP-82AH

FEATURES

* 4 in 1 professional environment instruments: 1. Air velocity 2. Air Temp. 3. Humidity 4. Dew point
* Tiny bone shape with lightweight and small size case design are suitable for handling with one hand.
* Wristlet design provides extra protection to the instrument especially for user one hand operation.
* Low-friction ball bearing mounted wheel design provides high accuracy at high and low air velocity.
* High precision humidity sensor with fast response time.
* Built- in microprocessor circuit assures excellent performance and accuracy.
* Concise and compact buttons arrangement, easy operation.
* Memorize the maximum and minimum value with recall.
* °C/°F detection by pressing button on the front panel.
* Hold function to freeze the current reading value.

GENERAL SPECIFICATIONS

Display	8 mm LCD display
Measurement	1. Air velocity 2. Air Temp. 3. Humidity 4. Dew point
Operating Humidity	Max. 80% RH.
Operating Temperature	0 to 50° C (32 to 122° F)
Over Input Display	Indication of "- - - -"
Power Supply	CR 2032 DC 3V battery
Power Consumption	Approx. DC 5 mA
Weight	160g (battery included)
Dimension	HWD 120 x 45 x 20 mm (4.7 x 1.8 x 1.2 inch).

* Appearance and specifications listed in this brochure are subject to change without notice.

1307-SP82AH

Standard	Instruction Manual
Accessory	

ELECTRICAL SPECIFICATION (23 ± 5°C)

Air velocity, Air Temp.

Unit	Range	Resolution	Accuracy
ft/min	80 to 3937 ft/min	1 ft/min	± 3% F.S. @ F.S. : full scale
m/s	0.4 to 20.0 m/s	0.1 m/s	
km/h	1.4 to 72.0 km/h	0.1 km/h	
MPH	0.9 to 44.7 mile/h	0.1 MPH	
knots	0.8 to 38.8 knots	0.1 knots	
Temp.	0 to 50 °C	0.1 °C	
	32 to 122 °F	0.1 °F	

Remark :

ft/min : feet per minute

MPH : miles per hour

m/s : meters per second

knots : nautical miles per hour

km/h : kilometers per hour

Humidity/Temp.

Unit	Range	Resolution	Accuracy
% RH	10 to 95 %RH	0.1 %RH	< 70% RH : ± 4 %RH ≥ 70% RH : ± (4 %rdg +1.2 %RH)
Temp.	0 to 50 °C	0.1 °C	± 1.2 °C
	32 to 122 °F	0.1 °F	± 2.5 °F

Dew point Temp.

Unit	Range	Resolution	Remark
°C	-25.3 to 49.0 °C	0.1 °C	* Calculate from the humidity/Temp. value
°F	-13.5 to 120.0 °F	0.1 °F	

Please refer to http://en.wikipedia.org/wiki/Dew_point